



Product Information Sheet

Air Operated Oil Transfer

Wall Mounted Transfer Kit



- Wall mounted kit
- Suitable for dispensing oil to mobile installations with optional hose and nozzle or directly through hose reels
- Supplied with all required fittings and accessories for connection of pump to the air and from tank to pump
- Rigid suction tube with 2 metre hose assembly

Optional:

- To make suction tube longer use DITIET10200 or DITI10500 in conjunction with DITIET10001 and DITIET10003
- If longer suction hose is required then will need DITIWB10004, DITIWB10002, hose clips YS295-040 and hose DITIPVC25



Equipped with Lubricator



MODEL	DITI1700111	DITI1700211	DITI1700311
Drum application	Wall mounted	Wall mounted	Wall mounted
Pressure ratio	1:1	3:1	5:1
Working pressure	20-115psi	20-115psi	20-115psi
Air consumption	@115psi 3.6 CFM	@115psi 3.9 CFM	@115psi 4.5 CFM
Max flow rate (per min)	18 litres	12 litres	14 litres
Suction tube diameter	42mm	42mm	42mm
Suction tube length	95mm	270mm	270mm
Air inlet connection	¼" BSP Female	¼" BSP Female	¼" BSP Female
Oil outlet connection	½" BSP Male	½" BSP Male	½" BSP Male
Maximum SAE viscosity	SAE 120	SAE 150	SAE 240
KIT BREAKDOWN			
Air operated oil pump	DITI1701001	DITI1701031	DITI1701051
Lubricator	DITIBL2000	DITIBL2000	DITIBL2000
Suction hose	DITIPVC1000MF2	DITIPVC1000MF2	DITIPVC1000MF2
Wall bracket	DITIWB10001	DITIWB10001	DITIWB10001
940mm suction tube	DITIWB10005	DITIWB10005	DITIWB10005
Bung adaptor	DITIBG00001	DITIBG00001	DITIBG00001
1" x 1" male nipple	DBN25	DBN25	DBN25
1" x 1" elbow	DBE2525MF	DBE2525MF	DBE2525MF
Top elbow nipple connector	DITIWBT00001	DITIWBT00001	DITIWBT00001
Foot valve	DITIFV00001	DITIFV00001	DITIFV00001
Foot strainer	DITIFR00001	DITIFR00001	DITIFR00001