



Product Information Sheet

Air Operated Oil Transfer



Equipped with Lubricator

1:1 Air Operated Oil Pump

- Suitable for oil bars, 205 litre drums and bulk tanks
- Air operated for integration into transfer system
- Smart design with fewer parts for less pump wear offering long life
- Differential air motor ensures smooth pumping
- Typical fluids handled include motor oil, synthetic oil, hydraulic oil, automatic transmission fluid and coolant
- Suitable for oil up to SAE 120
- Supplied with adjustable 2" bung adaptor
- Not suitable for pumping distances of more than 6 metres when reasonable volume is required



DIT11701001



DIT11701003



DIT11701004



DIT11701006

MODEL	DIT11701001	DIT11701003	DIT11701004	DIT11701006
Drum Application	Stub	205 litre drum	Stub	205 litre drum
Pressure ratio	1:1	1:1	1:1	1:1
Working pressure	70-115psi	70-115psi	70-115psi	70-115psi
Air consumption	@115psi 3.6 CFM	@115psi 3.6 CFM	@115psi 4.7 CFM	@115psi 4.7 CFM
Max flow rate (per min)	18 litres	18 litres	32 litres	32 litres
Suction tube diameter	42mm	42mm	42mm	42mm
Suction tube length	270mm	940mm	270mm	940mm
Air inlet connection	¼" BSP Female	¼" BSP Female	¼" BSP Female	¼" BSP Female
Oil outlet connection	½" BSP Male	½" BSP Male	¾" BSP Male	¾" BSP Male