

## Diaphragm Pumps

### Air Operated Double Diaphragm Pump

- Air operated diaphragm pump to transfer high volumes of fluids from drums or tanks
- Suitable for oil, diesel, coolant, ATF, waste oil and water
- Heavy duty construction with ground capability to eliminate static discharge
- Both metal & plastic bodies are available
- Maximum diameter solid: 1/8"
- A variety of elastomer options including Buna-N (Nitrile), Viton, EPDM & PTFE are available to meet abrasion, temperature and chemical compatibility concerns
- Viton, EPDM & PTFE are available on request
- DIT117150600 & DIT117150601 - 3/4" inlet/outlet, also supplied with 1/2" reducer



DIT117151200



DIT117151201



DQBY40AAB, DQBY 50AAB



DIT117150600N



DIT117150601V



DQBY15PPTF, DQBY 25PPTF

MODEL	Material	Max flow	Seals	Max	Inlet/Outlet	Air Inlet
DQBY15PPTF	Polypropylene	20 LPM	Teflon	100psi	1/2"	1/4"
DIT117150600N	Aluminium	45 / 60 LPM	Buna	115psi	1/2" / 3/4"	1/4"
DIT117150601V	Polypropylene	45 / 60 LPM	Viton	115psi	1/2" / 3/4"	1/4"
DIT117151200	Aluminium	90 LPM	Buna	115psi	1"	1/4"
DIT117151201	Polypropylene	90 LPM	Buna	115psi	1"	1/4"
DQBY25PPTF	Polypropylene	40 LPM	Teflon	100psi	1"	1/4"
DQBY40AAB	Aluminium	135 LPM	Buna	100psi	1 1/2"	1/4"
DQBY50AAB	Aluminium	200 LPM	Buna	100psi	2"	1/4"