



P U M P M O R E F O R L E S S

Product Information

Mobile Diesel Tank System

DOT 8123



- For transport, according to ADR, storage and fuelling of diesel fuel
- Double wall tank from HDPE with integrated sheet steel collection tray
- Approved for fuelling in water-protected areas (national installation laws and conditions are to be observed)
- Optical leakage detector
- Integrated carry handle
- Stable steel sheet pallet for driving under with forklift or hand-forklift
- Lower centre of gravity for higher stability and safer transport and handling
- Lockable hood
- 340 Litre Capacity
- Dimensions 128L x 79W x 87H (cm)
- Weight Approx. 89Kg

The standard model consists of the tank alone, however it can be customized with the products below to suit your needs.

12 & 24 Volt Pump



DTUT 1202 DTUT 2402

- Heavy duty portable DC transfer pump
- Manual nozzle, hanger, and bypass valve
- Pumps approximately 57 litres per minute
- Telescopic suction pipe and strainer
- 2" Bung thread to suit 205 litre drums
- 4 metres of fuel delivery hose

240 Volt Pump



SDFR 700G

- Heavy duty portable AC transfer pump
- Manual nozzle, hanger, and bypass valve
- Pumps approximately 75 litres per minute
- Telescopic suction pipe and strainer
- 2" Bung thread to suit 205 litre drums
- 4 metres of fuel delivery hose

Flow Meter



DTUT 807CLI

- Large easy to read 3 digit display and 6 digit totaliser
 - High accuracy $\pm 1\%$, weatherproof and corrosion resistant
 - Handles: Petrol, diesel, light oils, mineral spirits, heptane and hexane
 - Flow rate: 19 litres per minute minimum — 76 litres per minute maximum
 - Ideal for gravity feed situations as well as use with electric pumps
- Note: Not suitable for bleach, hydrochloric acid, ink, motor oil, and salt water